

# 180 °C series – Heat shield enclosures

## Housings and hoods

size **104.62**Specialized  
Applications

CE UK

BUREAU  
DNV VERITAS

EN 60529	IP65
UL 50 / UL 50E	Type 12 / 4
Ambient temperature limits	-40 °C ... +180 °C
Mechanical life (cycles)	≥ 500

CULUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	<a href="#">CHIR 48 L</a>	<a href="#">CHIR 48 LS</a>		
	Surface mounting housings, 1 lever and gasket, high construction, with or without metal cover	<a href="#">MHPR 48 L40</a>	<a href="#">MHPR 48 LS40</a>	M40 x 2	
	Hoods, 2 pegs, without gasket, side or top entry, high construction	Side entry <a href="#">MFOR 48 L40</a>	Top entry <a href="#">MFVR 48 L40</a> <a href="#">MFVR 48 L63</a>	M40 M63	

Inserts size 2 × (104.27)	Poles	Pages
CNE RY + RYN 16 A	48 + ⊕	I.9
CX RY 80 A / 16 A	4/8 + ⊕	I.13