

C-TYPE series

Hoods – 2 levers – without gasket

size **104.27**
**Heavy-Duty
Applications**






CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 levers, without gasket, side entry	MHO 24 X25 MHO 24 X32 CHO 24 X		M25 M32 Pg 21	 120 180 91 58,5
	Hoods, 2 levers, without gasket, top entry		MHV 24 X25 MHV 24 X32 CHV 24 X	M25 M32 Pg 21	 120 180 93 58,5
	Hoods, 2 levers, without gasket, side entry, high construction	MAO 24 X32 MAO 24 X40 CAO 24 X CAO 24 X29		M32 M40 Pg 21 Pg 29	 120 180 103 58,5
	Hoods, 2 levers, without gasket, top entry, high construction		MAV 24 X32 MAV 24 X40 CAV 24 X CAV 24 X29	M32 M40 Pg 21 Pg 29	 120 180 114,5 58,5

C-TYPE

E

Inserts size 104.27	Poles	Pages
CNE	16 A	24 + ☉ B.41
CCE	16 A	24 + ☉ B.47
CSH / JSH S	16 A	24 + ☉ B.55,61
CSHT	16 A	24 + ☉ B.68
CQE / CQEY	16 A	46 + ☉ B.75,85
CQEE	16 A	64 + ☉ B.79
CD	10 A	64 + ☉ B.91
CDD	10 A	108 + ☉ B.97
CDSH	10 A	42 + ☉ B.105

Inserts size 104.27	Poles	Pages
CSS	16 A	24 + ☉ B.121
CMCE / CMSH	16 A	10 + 2 (aux.) + ☉ B.146,151
CX	100 A/16 A	8/0 and 6/6 + ☉ B.156-157
CX / CXC	80 A/16 A	4/8 + ☉ B.161-162

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 06 T (6-slot sized MIXO frames)	C.95

Accessories:


CHCP 24
Dust protection
cover
Page G.46