

C-TYPE series

Special enclosures

size **104.27**
**Heavy-Duty
Applications**

CE UK


EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 4 pegs, without gasket, 2 top or frontal entries, high construction	Frontal entries	Top entries	
	To be used only with complete cable glands	MFF 24.225 CFF 24.221	MFV 24.232 CFV 24.221	
	Hoods, 4 pegs, without gasket, frontal entry, high construction	Frontal entry		
	Inclined hoods, 4 pegs, without gasket, side or top entry, high construction	Side entry	Top entry	
	To be used only with a complete cable gland	MIO 24.40 MIO 24.50 CIO 24.36	MIV 24.40 MIV 24.50 CIV 24.36	
	Enlarged hoods, 4 pegs, without gasket, side or top entry	Side entry	Top entry	
	To be used only with a complete cable gland	MQO 24.40 CQO 24	MQV 24.40 CQV 24	
	Hoods for ribbon cable, 4 pegs, without gasket, top entry and seal gaskets for ribbon cable hoods (supplied separately)	Hood		
	These enclosures grant IP44 only	CAN 24 Ribbon seal CRN 1 CRN 2 CRN 3 CRN P	Size (mm) 18,8 × 5,8 63,8 × 5,1 36,0 × 9,0 not pre-drilled	

Inserts size 104.27	Poles	Pages
CNE	16 A	24 + ☉ B.41
CCE	16 A	24 + ☉ B.47
CSH / JSH S	16 A	24 + ☉ B.55,61
CSHT	16 A	24 + ☉ B.68
CQE / CQEY	16 A	46 + ☉ B.75,85
CQEE	16 A	64 + ☉ B.79
CD	10 A	64 + ☉ B.91
CDD	10 A	108 + ☉ B.97
CDSH	10 A	42 + ☉ B.105

Inserts size 104.27	Poles	Pages
CSS	16 A	24 + ☉ B.121
CMCE / CMSh	16 A	10 + 2 (aux.) + ☉ B.146,151
CX	100 A/16 A	8/0 and 6/6 + ☉ B.156-157
CX / CXC	80 A/16 A	4/8 + ☉ B.161-162

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 06 T (6-slot sized MIXO frames)	C.95

Accessories:


CHCP 24
 Dust protection
 cover
 Page G.46