

Metallic – CKA / MKA

Housings – 1 lever – fixing by 4 screws

size **21.21**
**Heavy-Duty
Applications**


EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK

(pending: CQC, DNV and BV)

(pending: cURus)

Item	Description	Part No.	Entry	Dimension
	Angled bulkhead mounting housings, 1 stainless steel rigid lever or 1 galvanized rigid lever, fixing by 4 screws	Stainless steel rigid lever CKAXX 03 IA4		
		Galvanized rigid lever CKA 03 IA4		
	Angled surface mounting housings, 1 stainless steel rigid lever or 1 galvanized rigid lever, with cable entry, fixing by 4 screws, with <u>open bottom flange</u>	Stainless steel rigid lever MKAXX IAP25	M25	
		Galvanized rigid lever MKA IAP25	M25	
	Angled surface mounting housings, 1 stainless steel rigid lever or 1 galvanized rigid lever, with cable entry, fixing by 4 screws, with <u>closed bottom flange</u>	Stainless steel rigid lever MKAXX AP25	M25	
		Galvanized rigid lever MKA AP25	M25	

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25
CJ (RJ45)	1 A to 2,1 A	A.30-33
CUK (USB)	–	A.36
CLK (Fibre optics)	–	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12 - CUK 2FT /3FT
- CJ KF - CLK 04 SCF /SCF-H /SCM
- CJK 8FT /8IFT

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67