






CQEY 32 + CQEY 32 N
16 A 500 V

size **77.62**
64 poles + ⊕

Tool-less connection – AXYR®

EN 61984 rating	16 A 500 V 6 kV 3
	16 A 830 V 8 kV 2
Rated voltage (UL / CSA)	600 V
Insulation resistance	≥ 10 GΩ
Contact resistance	≤ 3 mΩ
Ambient temperature limit	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK (pending: EAC)
(pending: CQC, DNV and BV)
(pending: cURus)

Item	Description	Part No.	Dimension
	Male inserts, No. (1-32) Male inserts, No. (33-64) Spring/AXYR® push-in connection	CQEYM 32 CQEYM 32 N	
	Female inserts, No. (1-32) Female inserts, No. (33-64) Spring/AXYR® push-in connection	CQEYF 32 CQEYF 32 N	

Materials	
Insert	polycarbonate (PC)
UL 94 flame rating	V-0
Colour	pebble grey, RAL 7032
Contacts	built-in, copper alloy, silver ● plated

Wiring information	
Wire cross sectional area	
- unprepared	0,25 mm² - 4 mm² (AWG 24-12)
- prepared	0,25 mm² - 2,5 mm² (AWG 24-14)
Stripping length	9...11 mm
Wire diameter: up to 5 mm.	



CR Q08E
Coding pins
Page G.8

Enclosures size 77.62	Pages 
Heavy-Duty Applications	
Metallic with C-TYPE lever	E.78-83
Aggressive Environments	
Metallic W-TYPE with C-TYPE lever	E.166-167
Metallic E-Xtreme® with C-TYPE lever	E.190-191

