

CSH 10

16 A 500 V





size **57.27****10 poles +** 

Tool-less connection – SQUICH®

EN 61984 rating	16 A 500 V 6 kV 3
	16 A 400 / 690 V 6 kV 2
Rated voltage (UL / CSA)	600 V
Insulation resistance	≥ 10 GΩ
Contact resistance	≤ 3 mΩ
Ambient temperature limit	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK EAC

ECBT2.E115072 | ECBT8.E115072
PVVA2.E506437 | PVVA8.E506437

Item	Description	Part No.	Dimension
	Male inserts with male contacts Spring clamp connections, with actuator button	CSHM 10	
	Female inserts with female contacts Spring clamp connections, with actuator button	CSHF 10	

Materials

Insert	polycarbonate (PC)
UL 94 flame rating	V-0
Colour	pebble grey, RAL 7032
Contacts	built-in, copper alloy, silver ● plated

Wiring information

Wires cross sectional area	
- unprepared	0,14 mm ² - 2,5 mm ² (AWG 26-14)
- prepared	0,14 mm ² - 2,5 mm ² (AWG 26-14)
Stripping length	9...11 mm

Enclosures size 57.27

Pages

Heavy-Duty Applications


Metallic with C-TYPE lever	E.54-61
Metallic with IL-BRID lever	E.92-95,105
Metallic with JEI®-P lever	E.113-114,119
Metallic with V-TYPE IP67 lever	E.125,130-131
Thermoplastic T-TYPE	E.228-229,234-235

Aggressive Environments

Metallic IP68 high protection	E.144-145
Metallic W-TYPE	E.156-157,163
Metallic E-Xtreme®	E.176-177,184-185,195
Thermoplastic T-TYPE/W	E.228-229,234-235

Specialized Applications

EMC (Electromagnetic Shielding)	E.210-211,217
Hygienic series for food and beverage	E.245,248
Standard applications with Central lever	E.256-257
BIG Enclosures for multiple cable entries	E.269,274-275
COB system for switch cabinet	E.286-289
Light and Sound applications with JEI®-P lever	E.298-299



CSH 10 inserts max. current load derating diagram