

Crimp connection

Insulating resistance	≥ 10 GΩ
Ambient temperature limit	-40 °C ... +70 °C
Cable operating temperature	-5 °C ... +55 °C
Cable storage temperature	-30 °C ... +70 °C
Cable installation temperature	-5 °C ... +50 °C
Cable flame retardancy according to:	IEC 60332-1
Halogen-free according to:	IEC 60754-2
Mechanical life (cycles)	≥ 500

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	L(m)	Dimension
	Adapter male insert for 4 SC contacts To be used with hoods with glued gasket, DESINA® version	CLK 04 SCM		
	Adapter female insert with ceramic sleeve, for 4 SC contacts	CLK 04 SCF		
	Adapter female insert with metal sleeve, for 4 SC contacts	CLK 04 SCF-H		
	SC contact for single-mode fibre E9/125 µm	CL 9/125 SC		
	SC contact for multi-mode fibre G50/125 µm or G62,5/125 µm	CL 125 SC		
	SC contact for 1 mm Ø POF	CL POF SC		
	SC duplex patch cord, single-mode fibre E9/125 µm, yellow cable	CW 1 SC9 CW 2 SC9 CW 3 SC9 CW 5 SC9 CW 10 SC9	1 2 3 5 10	
	SC duplex patch cord, multi-mode fibre G50/125 µm, orange cable	CW 1 SC50 CW 2 SC50 CW 3 SC50 CW 5 SC50 CW 10 SC50	1 2 3 5 10	
	SC duplex patch cord, multi-mode fibre G62,5/125 µm, orange cable	CW 1 SC62 CW 2 SC62 CW 3 SC62 CW 5 SC62 CW 10 SC62	1 2 3 5 10	

Materials

Insert	polycarbonate (PC)
Cable	polyvinyl chloride (PVC)
UL 94 flame rating	V-0
Colour	pebble grey, RAL 7032

Notes:

- Adapter inserts designed to be used with SC contacts;
- SC contact for SI (Step Index) FIBRE (HCS®) 200/230 µm: **CL 230 SC** (on request);
- base equipment for SC contact GI FIBRE: **CLKZ 125 SC** (If this application is required, please contact ILME S.p.A.
- supplementary set for POF: **CLKZ POF**, to be ordered with **CLKZ 125 SC** (If this application is required, please contact ILME S.p.A.

Compact 21.21 enclosures	Pages
Heavy-Duty Applications	
Thermoplastic	A.46-48,51-52*
Thermoplastic with metal lever	A.53-55
Metallic	A.56-63,65-66*
Aggressive Environments	
Metallic IP68 high protection	A.78-81
Specialized Applications	
Hygienic series for food and beverage	A.94-96*

* male inserts without gasket compatible only with hoods with glued gasket, **DESINA®** version

Inserts already supplied with stainless steel fixing screw with gasket, which ensures IP66/IP67/IP69 degree of protection