






CW / CWC

RJ45 patch cord Cat. 5, 6_A and 7

Ambient temperature limit -40 °C ... +75 °C

Item	Description	Part No.	L(m)	Dimension
	2xRJ45 male connector with 8 data contacts, S/FTP Cat. 6 _A cable 4x2 AWG 27/7 - Shielded Material PUR	CW 1 J2M87	1	
		CW 2 J2M87	2	
		CW 3 J2M87	3	
		CW 5 J2M87	5	
		CW 7.5J2M87	7,5	
		CW 10 J2M87	10	
		CW 15 J2M87	15	
	2xRJ45 cable plug SF/UTP Cat. 5 cable 4x2 AWG 26/7 - Shielded Material PUR	CW J5 1M	1	
		CW J5 2M	2	
		CW J5 3M	3	
		CW J5 5M	5	
		CW J5 7.5M	7,5	
		CW J5 10M	10	
		CW J5 15M	15	
	2xRJ45 cable plug SF/UTP Cat. 5 cable 4x2 AWG 26/7 - Shielded Material PVC	CWC J5 1M	1	
		CWC J5 2M	2	
		CWC J5 3M	3	
		CWC J5 5M	5	
		CWC J5 7.5M	7,5	
		CWC J5 10M	10	
		CWC J5 15M	15	
	2xRJ45 cable plug S/FTP Cat. 6 _A cable 4x2 AWG 27/7 - Shielded Material PVC	CWC J6 1M	1	
		CWC J6 2M	2	
		CWC J6 3M	3	
		CWC J6 5M	5	
		CWC J6 7.5M	7,5	
		CWC J6 10M	10	
		CWC J6 15M	15	
	1xM12 + 1xRJ45 cable plugs S/FTP Cat. 7 cable Over moulded IP67 to RJ45 plug IP20 4x2 AWG 26/7 Material PUR	CW XJ0.5M	0,5	
		CW XJ1M	1	
		CW XJ2M	2	
		CW XJ3M	3	
		CW XJ5M	5	
		CW XJ7.5M	7,5	
		CW XJ10M	10	

Materials

Cable	hard polyurethane foam (PUR)
Shielding	polyvinyl chloride (PVC)
Colour	nickel-plated brass
	green, RAL 6018

CW wiring diagram

1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
VS	VS