

CX 03 MP



Inserts for metal pneumatic contacts

size **1 module**

Insulation resistance	≥ 10 GΩ
Ambient temperature limit	-40 °C ... +80 °C
Mechanical life (cycles)	≥ 500



(pending: cURus)

Item	Description	Part No.	Dimension
	<p>Inserts with 3 housings for tube Ø 3 - 4 - 6 mm</p> <p>Without contacts (to be ordered separately)</p>	CX 03 MP	

Materials

Insert	polycarbonate (PC)
UL 94 flame rating	V-0
Colour	blue, RAL 5015

Accessories**MIXO Frames**

	Pages
Metal frames for modular units	C.94-95
Thermoplastic docking frames	C.98-101

Enclosures

Insulating MIXO holder	C.103
MIXO ONE	C.106-107
MIXO TWO	C.110-111

- Identical male and female modular units; female contacts with or without closing valve;
- pneumatic contacts for pressure values up to 10 bar, for use with clean and dry compressed air;
- use of tubes with Ø 3 - 4 and 6 mm, and replacement of tubes with assembled units;
- possibility of using tubes with different diameters in the same modular unit;
- coding and guiding pins must be used for pneumatic contacts modules (**CRM CX / CRF CX**);
- these pins also provide coding if pneumatic contacts modules are used exclusively;
- the use of pneumatic contacts requires an appropriate filtering and dehydration system to prevent dangerous condensation;
- available in **HNM version** up to 10.000 mating cycles.