

Slim enclosures – Rigid lever – IP67

size **66.16**

Housings and covers – 1 lever

**Heavy-Duty
Applications**


EN 60529	IP65 / IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 stainless steel rigid lever, without gasket, with or without metal cover	CZ7L 25 L	CZ7L 25 LS		
	Surface mounting housings, 1 stainless steel rigid lever, without gasket, with or without metal cover	MZ7P 25 L25 MZ7P 25 L225	MZ7P 25 LS25 MZ7P 25LS225	M25 M25 × 2	
	Cover, 1 stainless steel rigid lever, without gasket Covers cannot be used together with metal coding pins For enclosures with 2 pegs and gasket with loop for hoods	CZ7C 25 LG			

CZ7 / MZ7

E

Inserts size 66.16	Poles	Pages
CDA 16 A	16 + ⊕	B.17
CDC 16 A	16 + ⊕	B.20
CSAH 16 A	16 + ⊕	B.25
CD 10 A	25 + ⊕	B.31
CDD 10 A	38 + ⊕	B.33

Note:

The rigid lever offers an IP66/IP67/IP69 degree of protection (according to EN 60529) when fitted with a complete and coupled connector and used with ILME standard hoods in die cast aluminum with pegs (without adapter).

Complete with:

Hoods
Page E.17

Covers
Page E.17