

JEI®-P series

Housings and hoods – 1 lever – with gasket

size **44.27**Heavy-Duty
Applications

CE UK

EN 60529	IP65
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

(pending CQC)

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	JPI 06 L	JPI 06 LS		
	Surface mounting housings, 1 lever and gasket	JMPP 06 L20 JMPP 06 L220		M20 M20 × 2	
	Surface mounting housings, 1 lever and gasket, high construction To be used only with a complete cable gland	JMPAP 06 L25 JMPAP 06 L225 JMPAP 06 L32 JMPAP 06 L232 JMPAP 06 L40 JMPAP 06 L240		M25 M25 × 2 M32 M32 × 2 M40 M40 × 2	
	Hoods, 1 lever and gasket, top entry		Top entry JMPV 06 LG25	M25	
	Hoods, 1 lever and gasket, side or top entry, high construction To be used only with a complete cable gland	Side entry JMPFO 06LG40	Top entry JMPFV 06LG25 JMPFV 06LG32 JMPFV 06LG40	M25 M32 M40	

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118
CT / CTSE*	16 A 6 + ⊕	B.126,130

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Complete with:


Hoods
Page E.49

Covers
Page E.52