

E-Xtreme® – V-TYPE lever version

Housings – 1 lever – with gasket

size **44.27**
3 000 hrs resistance
in salt-spray tests

Aggressive
Environments


EN 60529	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C*
with silicone gasket (on request)	-60 °C ... +125 °C*
Mechanical life (cycles)	≥ 500

*(>125 °C up to 180 °C with RY inserts)




CE UK

BUREAU
VERITAS

(pending: CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	C7IE 06 L		
	Surface mounting housings, 1 lever and gasket,  2 000 hrs	M7PE 06 L20 M7PE 06 L220	M20 M20 × 2	
	Surface mounting housings, 1 lever and gasket, high construction  2 000 hrs	M7APE 06 L32 M7APE 06L232 M7APE 06 L40 M7APE 06L240	M32 M32 × 2 M40 M40 × 2	

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	6 + ⊕	B.38	MIXO modules	C.12-93
CCE 16 A	6 + ⊕	B.44	CX 02 T (2-slot sized MIXO frames)	C.95
CSH / JSH S	16 A	6 + ⊕		
CQE / CQEY	16 A	10 + ⊕		
CDD 10 A	24 + ⊕	B.94		
CDSH / CDSH NC	10 A	9 and 6 + ⊕		
CSS 16 A	6 + ⊕	B.118		
CT / CTSE*	16 A	6 + ⊕		

180 °C Inserts size 44.27	Poles	Pages
CNE RY** 16 A	6 + ⊕	I.5

** >125 °C up to 180 °C

*can be used only in bulkhead mounting housings