

E-Xtreme® – V-TYPE lever version

Housings – 2 levers – with gasket

size **77.27**
3 000 hrs resistance
in salt-spray tests

Aggressive
Environments


EN 60529	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C*
with silicone gasket (on request)	-60 °C ... +125 °C*
Mechanical life (cycles)	≥ 500

*(>125 °C up to 180 °C with RY inserts)





CE UK

BUREAU
VERITAS

(pending: CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 2 levers and gasket Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	C7IE 16		
	Surface mounting housings, 2 levers and gasket  2 000 hrs	M7PE 16.25 M7PE 16.225	M25 M25 × 2	
	Surface mounting housings, 2 levers and gasket, high construction  2 000 hrs	M7APE 16.32 M7APE 16.232 M7APE 16.40 M7APE 16.240	M32 M32 × 2 M40 M40 × 2	

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ⊕	B.40	CP / CPY 35 A	6 + ⊕	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ⊕	B.46	CSS 16 A	16 + ⊕	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ⊕	B.54,60	CT / CTSE* 16 A	16 + ⊕	B.128,132		
CSHT 16 A	16 + ⊕	B.67	CT / CTS* 10 A	40 + ⊕	B.138,140		
CQE / CQEY 16 A	32 + ⊕	B.74,84	CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150	180 °C Inserts size 77.27	Poles Pages
CQEE 16 A	40 + ⊕	B.78	CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160	CNE RY**	16 A 16 + ⊕ I.7
CD 10 A	40 + ⊕	B.90				CP RY**	35 A 6 + ⊕ I.10
CDD 10 A	72 + ⊕	B.94				CX RY**	80 A 4 + ⊕ I.11
CDSH 10 A	27 + ⊕	B.104				CX RY**	80 A/16 A 4/2 + ⊕ I.12

*can be used only in bulkhead mounting housings

** >125 °C up to 180 °C