

C-TYPE series

Housings – 4 pegs – with gasket

size **77.27**
**Heavy-Duty
Applications**


CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CALUS ECBT2.E115072 | ECBT8.E115072

Item	Description	Metal cover	Plastic cover	Entry	Dimension
	Bulkhead mounting housings, 4 pegs and gasket, with or without metal or plastic cover	CHI 16 CS	CHI 16 CP		
	Enclosures with plastic cover do not have UL approval	Without Cover	CHI 16 C		
	Surface mounting housings, 4 pegs and gasket, with metal or plastic cover	MHP 16 CS25 MHP 16 CS225 CHP 16 CS CHP 16 CS2	MHP 16 CP25 MHP 16 CP225 CHP 16 CP CHP 16 CP2	M25 M25 × 2 Pg 21 Pg 21 × 2	
	Enclosures with plastic cover do not have UL approval				
	Surface mounting housings, 4 pegs and gasket, with metal or plastic cover, high construction	MAP 16 CS32 MAP 16 CS232 MAP 16 CS40 MAP 16 CS240 CAP 16 CS CAP 16 CS2 CAP 16 CS29 CAP 16 CS229	MAP 16 CP32 MAP 16 CP232 MAP 16 CP40 MAP 16 CP240 CAP 16 CP CAP 16 CP2 CAP 16 CP29 CAP 16 CP229	M32 M32 × 2 M40 M40 × 2 Pg 21 Pg 21 × 2 Pg 29 Pg 29 × 2	
	Enclosures with plastic cover do not have UL approval				

C-TYPE

E

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ☉	B.40	CP / CPY 35 A	6 + ☉	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ☉	B.46	CSS 16 A	16 + ☉	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ☉	B.54,60	CT / CTSE* 16 A	16 + ☉	B.128,132		
CSHT 16 A	16 + ☉	B.67	CT / CTS* 10 A	40 + ☉	B.138,140		
CQE / CQEY 16 A	32 + ☉	B.74,84	CMCE / CMSH 16 A	6 + 2 (aux.) + ☉	B.145,150		
CQEE 16 A	40 + ☉	B.78	CX / CXC 80 A/16 A	4/0, 4/2 + ☉	B.158-160		
CD 10 A	40 + ☉	B.90	CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ☉	B.163-164, 168-169		
CDD 10 A	72 + ☉	B.94					
CDSH 10 A	27 + ☉	B.104					

*can be used only in bulkhead mounting housings

Accessories:

CHCP 16
Dust protection
cover
Page G.46