

W-TYPE series

Hoods and covers – 4 pegs – without gasket

size **77.27**Aggressive
Environments












CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, without gasket, side entry	MHOW 16.25 MHOW 16.32 CHOW 16		M25 M32 Pg 21	 
	Hoods, 4 pegs, without gasket, top entry To be used only with a complete cable gland		MHVW 16.25 MHVW 16.32 CHVW 16	M25 M32 Pg 21	 
	Hoods, 4 pegs, without gasket, side or top entry, high construction	MAOW 16.32 MAOW 16.40 CAOW 16.29	MAVW 16.32 MAVW 16.40 CAVW 16.29	M32 M40 Pg 29	 
	Hoods, 4 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFOW 16.32 MFOW 16.40	MFVW 16.32 MFVW 16.40	M32 M40	 
	Covers, 4 pegs, without gasket For enclosures with 2 levers and gasket with loop for hoods  or with eyelet for housings 	With loop CHCW 16 S	With eyelet CHCW 16		 

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	16 + ⊕	B.40	CP / CPY 35 A	6 + ⊕	B.112,114	MIXO modules	C.12-93
CCE 16 A	16 + ⊕	B.46	CSS 16 A	16 + ⊕	B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	16 + ⊕	B.54,60	CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150		
CSHT 16 A	16 + ⊕	B.67	CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160		
CQE / CQEY 16 A	32 + ⊕	B.74,84					
CQEE 16 A	40 + ⊕	B.78	CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ⊕	B.163-164, 168-169		
CD 10 A	40 + ⊕	B.90					
CDD 10 A	72 + ⊕	B.94					
CDSH 10 A	27 + ⊕	B.104					

Accessories:



CHCP 16
Dust protection
cover
Page G.46