

C-TYPE series

Special enclosures

size **77.27**
**Heavy-Duty
Applications**


CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 4 pegs, without gasket, 2 top or frontal entries, high construction To be used only with complete cable glands	Frontal entries	Top entries	
		MFF 16.225 CFF 16.221	MFV 16.220 MFV 16.225 CFV 16.216 CFV 16.221	
	Hoods, 4 pegs, without gasket, frontal entry, high construction To be used only with a complete cable gland	Frontal entry		
	Inclined hoods, 4 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	Side entry	Top entry	

Inserts size 77.27	Poles	Pages
CNE	16 A	16 + ☉ B.40
CCE	16 A	16 + ☉ B.46
CSH / JSH S	16 A	16 + ☉ B.54,60
CSHT	16 A	16 + ☉ B.67
CQE / CQEY	16 A	32 + ☉ B.74,84
CQEE	16 A	40 + ☉ B.78
CD	10 A	40 + ☉ B.90
CDD	10 A	72 + ☉ B.94
CDSH	10 A	27 + ☉ B.104

Inserts size 77.27	Poles	Pages
CP / CPY	35 A	6 + ☉ B.112,114
CSS	16 A	16 + ☉ B.120
CMCE / CMSH	16 A	6 + 2 (aux.) + ☉ B.145,150
CX / CXC	80 A/16 A	4/0, 4/2 + ☉ B.158-160
CX	40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ☉ B.163-164, 168-169

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 04 T (4-slot sized MIXO frames)	C.95

Accessories:


CHCP 16
Dust protection
cover
Page G.46