

C-TYPE series

Hoods – 2 pegs – without gasket



size **104.62**
**Heavy-Duty
Applications**

CE UK


EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life	≥ 500 cycles



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	MFO 48 L32 MFO 48 L40 MFO 48 L50 CFO 48 L29 CFO 48 L CFO 48 L42		M32 M40 M50 Pg29 Pg36 Pg42	
	To be used only with a complete cable gland				
	Hoods, 2 pegs, without gasket, top entry		MFV 48 L32 MFV 48 L40 MFV 48 L50 MFV 48 L63 CFV 48 L29 CFV 48 L CFV 48 L42	M32 M40 M50 M63 Pg 29 Pg 36 Pg 42	
	To be used only with a complete cable gland				

Inserts size (104.27) × 2	Poles	Pages	Inserts size (104.27) × 2	Poles	Pages
CNE 16 A	48 + ⊕	B.43	CMCE / CMSH 16 A	10 + 2 (aux.) + ⊕	B.148,153
CCE 16 A	48 + ⊕	B.49			
CSH / JSH S 16 A	48 + ⊕	B.57,63			
CQE / CQEY 16 A	92 + ⊕	B.77,87			
CD 10 A	128 + ⊕	B.93			
CDD 10 A	216 + ⊕	B.99			
CDSH 10 A	84 + ⊕	B.107			
CSS 16 A	48 + ⊕	B.123			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 06 T (6-slot sized MIXO frames) × 2		C.95