

E-Xtreme® – V-TYPE lever version

size **104.27**

Hoods – 4 pegs – without gasket

3 000 hrs resistance
in salt-spray tests

Aggressive
Environments






EN 60529	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C*
with silicone gasket (on request)	-60 °C ... +125 °C*
Mechanical life (cycles)	≥ 500

*(>125 °C up to 180 °C with RY inserts)

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, side entry	MHOE 24.25M MHOE 24.32M		M25 M32	
	Hoods, 4 pegs, top entry To be used only with a complete cable gland		MHVE 24.25M MHVE 24.32M	M25 M32	
	Hoods, 4 pegs, side or top entry, high construction To be used only with a complete cable gland	MFOE 24.32M MFOE 24.40M	MFVE 24.32M MFVE 24.40M	M32 M40	

E-Xtreme®

E

Inserts size 104.27	Poles	Pages
CNE	16 A	24 + ☉ B.41
CCE	16 A	24 + ☉ B.47
CSH / JSH S	16 A	24 + ☉ B.55,61
CSHT	16 A	24 + ☉ B.68
CQE / CQEY	16 A	46 + ☉ B.75,85
CQEE	16 A	64 + ☉ B.79
CD	10 A	64 + ☉ B.91
CDD	10 A	108 + ☉ B.97
CDSH	10 A	42 + ☉ B.105

Inserts size 104.27	Poles	Pages
CSS	16 A	24 + ☉ B.121
CMCE / CMSH	16 A	10 + 2 (aux.) + ☉ B.146,151
CX	100 A/16 A	8/0 and 6/6 + ☉ B.156-157
CX / CXC	80 A/16 A	4/8 + ☉ B.161-162

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 06 T (6-slot sized MIXO frames)	C.95

180 °C Inserts size 104.27	Poles	Pages
CNE RY**	16 A	24 + ☉ I.8
CX RY**	80 A/16 A	4/2 + ☉ I.13

** >125 °C up to 180 °C