

C-TYPE series

Hoods – 2 pegs – without gasket

size **44.27**
**Heavy-Duty
Applications**










CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	MHO 06 L20 MHO 06 L25 CHO 06 L13 CHO 06 L16		M20 M25 Pg 13,5 Pg 16	 
	Hoods, 2 pegs, without gasket, top entry To be used only with a complete cable gland		MHV 06 L20 MHV 06 L25 CHV 06 L13 CHV 06 L16	M20 M25 Pg 13,5 Pg 16	 
	Hoods, 2 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 06 L25 MFO 06 L32 MFO 06 L40 CFO 06 L21 CFO 06 L29	MFV 06 L25 MFV 06 L32 MFV 06 L40 CFV 06 L21 CFV 06 L29	M25 M32 M40 Pg 21 Pg 29	 
	Hoods, 2 pegs, without gasket, high construction, designed to be drilled	Without entry CAC 06 L			 

Inserts size 44.27	Poles	Pages
CNE	16 A	6 + ☉ B.38
CCE	16 A	6 + ☉ B.44
CSH / JSH S	16 A	6 + ☉ B.52,58
CQE / CQEY	16 A	10 + ☉ B.72,82
CDD	10 A	24 + ☉ B.94
CDSH / CDSH NC	10 A	9 and 6 + ☉ B.102,108
CSS	16 A	6 + ☉ B.118

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Accessories:



CHCP 06
Dust protection cover
Page G.46