

C-TYPE series

Hoods – 2 pegs – without gasket

size **57.27**
**Heavy-Duty
Applications**











CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	MHO 10 L20 MHO 10 L25 CHO 10 L16		M20 M25 Pg 16	 
	Hoods, 2 pegs, without gasket, top entry To be used only with a complete cable gland		MHV 10 L20 MHV 10 L25 CHV 10 L	M20 M25 Pg 16	 
	Hoods, 2 pegs, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 10 L32 MFO 10 L40 CFO 10 L21 CFO 10 L29	MFV 10 L32 MFV 10 L40 CFV 10 L21 CFV 10 L29	M32 M40 Pg 21 Pg 29	 
	Hoods, 2 pegs, without gasket, high construction, designed to be drilled	Without entry CAC 10 L			 

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CCE	16 A	10 + ☉ B.45	CX	40 A/10 A	8/24 + ☉ B.170-171
CSH / JSH S	16 A	10 + ☉ B.53,59			
CSHT	16 A	10 + ☉ B.66			
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Accessories:


CHCP 10
Dust protection
cover
Page G.46