

size **77.62**

Heavy-Duty Applications

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



CUL[®]US ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side or top entry	MFO 32.32	MFV 32.32	M32	
	To be used only with a complete cable gland	MFO 32.40	MFV 32.40	M40	
		MFO 32.50	MFV 32.50	M50	
		CFO 32.29	CFV 32.29	Pg 29	
		CFO 32	CFV 32	Pg 36	
		CFO 32.42	CFV 32.42	Pg 42	

Inserts size (77.27) × 2		Poles	Pages
CNE	16 A	32 + ⊕	B.42
CCE	16 A	32 + ⊕	B.48
CSH / JSH S	16 A	32 + ⊕	B.56,62
CQE / CQEY	16 A	64 + ⊕	B.76,86
CD	10 A	80 + ⊕	B.92
CDD	10 A	144 + ⊕	B.98
CDSH	10 A	54 + ⊕	B.106
CP / CPY	35 A	12 + ⊕	B.113,115

Inserts size (77.27) × 2		Poles	Pages
CSS	16 A	32 + ⊕	B.122
CMCE / CMSH	16 A	12 + 4 (aux.) + ⊕	B.147,152

MIXO Modular Inserts	Pages
MIXO Modules	C.12-93
CX 04 T (4-slot sized MIXO frames) × 2	C.95