

IP68 high protection series

Housings, hoods and covers – Screw locking

size **44.27**Aggressive
Environments








CE UK



EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, screw locking Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	CGI 06		
	Surface mounting housings, screw locking	MGP 06.32 CGP 06.29	M32 Pg 29	
	Hoods, side entry, screw locking To be used only with a complete cable gland	MGO 06.25 MGO 06.32 CGO 06.16 CGO 06.21 CGO 06.29	M25 M32 Pg 16 Pg 21 Pg 29	
	Hoods, top entry, screw locking To be used only with a complete cable gland	MGV 06.25 MGV 06.32 MGV 06.40 CGV 06.16 CGV 06.21 CGV 06.29	M25 M32 M40 Pg 16 Pg 21 Pg 29	
	Covers, screw locking, for housings or for hoods With loop 	For housings CGC 06 For hoods CGC 06 G		 

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118
CT / CTSE*	16 A 6 + ⊕	B.126,130

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Accessories:


CGCP FX
 Dust protection cover
 Page G.47

CGCP MB
 Dust protection cover
 Page G.47