

IP68 high protection series

Housings, hoods and covers – Screw locking

size **104.27**Aggressive
Environments

CE UK



EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, screw locking Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	CGI 24		
	Surface mounting housings, screw locking	MGP 24.40 MGP 24.240 CGP 24.36 CGP 24.236	M40 M40 x 2 Pg 36 Pg 36 x 2	
	Hoods, side entry, screw locking To be used only with a complete cable gland	MGO 24.32 MGO 24.40 MGO 24.50 CGO 24.21 CGO 24.29 CGO 24.36	M32 M40 M50 Pg 21 Pg 29 Pg 36	
	Hoods, top entry, screw locking To be used only with a complete cable gland	MGV 24.325 MGV 24.32 MGV 24.232 MGV 24.40 MGV 24.240 MGV 24.50 CGV 24.21 CGV 24.29 CGV 24.229 CGV 24.36	M25 x 3 M32 M32 x 2 M40 M40 x 2 M50 Pg 21 Pg 29 Pg 29 x 2 Pg 36	
	Covers, screw locking, for housings or for hoods With loop	For housings CGC 24	For hoods CGC 24 G	

Inserts size 104.27	Poles	Pages	Inserts size 104.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	24 + ⊕	B.41	CSS 16 A	24 + ⊕	B.121	MIXO modules	C.12-93
CCE 16 A	24 + ⊕	B.47	CT / CTSE* 16 A	24 + ⊕	B.129,133	CX 06 T (6-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	24 + ⊕	B.55,61	CT / CTS* 10 A	64 + ⊕	B.139,141		
CSHT 16 A	24 + ⊕	B.68	CMCE / CMSH 16 A	10 + 2 (aux.) + ⊕	B.146,151		
CQE / CQEY 16 A	46 + ⊕	B.75,85	CX 100 A/16 A	8/0 and 6/6 + ⊕	B.156-157		
CQEE 16 A	64 + ⊕	B.79	CX / CXC 80 A/16 A	4/8 + ⊕	B.161-162		
CD 10 A	64 + ⊕	B.91	*can be used only in bulkhead mounting housings				
CDD 10 A	108 + ⊕	B.97					
CDSH 10 A	42 + ⊕	B.105					

Accessories:



CGCP FX
Dust protection cover
Page G.47



CGCP MB
Dust protection cover
Page G.47