

IP68 high protection series

Housings, hoods and covers – Screw locking

size **57.27**Aggressive
Environments

CE UK



EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, screw locking	CGI 10		
	Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)			
	Surface mounting housings, screw locking	MGP 10.32 CGP 10.29	M32 Pg 29	
	Hoods, side entry, screw locking	MGO 10.25 MGO 10.32 CGO 10.16 CGO 10.21 CGO 10.29	M25 M32 Pg 16 Pg 21 Pg 29	
	To be used only with a complete cable gland			
	Hoods, top entry, screw locking	MGV 10.25 MGV 10.32 MGV 10.40 CGV 10.16 CGV 10.21 CGV 10.29	M25 M32 M40 Pg 16 Pg 21 Pg 29	
	To be used only with a complete cable gland			
	Covers, screw locking, for housings or for hoods	For housings CGC 10	For hoods CGC 10 G	
	With loop			

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ⊕ B.39	CT / CTSE*	16 A	10 + ⊕ B.127,131
CCE	16 A	10 + ⊕ B.45	CMCE / CMSH	16 A	3 + 2 (aux.) + ⊕ B.144,149
CSH / JSH S	16 A	10 + ⊕ B.53,59	CX	40 A/10 A	8/24 + ⊕ B.170-171
CSHT	16 A	10 + ⊕ B.66	*can be used only in bulkhead mounting housings		
CQE / CQEY	16 A	18 + ⊕ B.73,83			
CDD	10 A	42 + ⊕ B.95			
CDSH	10 A	18 + ⊕ B.103			
CSS	16 A	10 + ⊕ B.119			

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 03 T (3-slot sized MIXO frames)	C.95

Accessories:



CGCP FX
Dust protection
cover
Page G.47



CGCP MB
Dust protection
cover
Page G.47