

E-Xtreme® – IP68 high protection version

size **77.27**

Housings, hoods and covers – Screw locking

3 000 hrs resistance
in salt-spray testsAggressive
Environments

EN 60529	IP66 / IP68 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
with silicone gasket (on request)	-60 °C ... +125 °C*
Mechanical life (cycles)	≥ 500






*(>125 °C up to 180 °C with RY inserts)

CE UK



CFLUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, screw locking Optional mounting frame CG .. FL is available to ensure water tightness for bulkhead mounting housing when fitted onto a cabinet panel. (See page G.45)	CGIE 16		
	Surface mounting housings, screw locking	MGPE 16.40	M40	
	Hoods, side entry, screw locking	MGOE 16.32 MGOE 16.40 MGOE 16.50	M32 M40 M50	
	Hoods, top entry, screw locking	MGVE 16.25 MGVE 16.225 MGVE 16.32 MGVE 16.40 MGVE 16.50	M25 M25 × 2 M32 M40 M50	
	Covers, screw locking, for housings With loop 	CGCE 16		

Inserts size 77.27	Poles	Pages
CNE 16 A	16 + ⊕	B.40
CCE 16 A	16 + ⊕	B.46
CSH / JSH S 16 A	16 + ⊕	B.54,60
CSHT 16 A	16 + ⊕	B.67
CQE / CQEY 16 A	32 + ⊕	B.74,84
CQEE 16 A	40 + ⊕	B.78
CD 10 A	40 + ⊕	B.90
CDD 10 A	72 + ⊕	B.94
CDSH 10 A	27 + ⊕	B.104
CP / CPY 35 A	6 + ⊕	B.112,114

Inserts size 77.27	Poles	Pages
CSS 16 A	16 + ⊕	B.120
CT / CTSE* 16 A	16 + ⊕	B.128,132
CT / CTS* 10 A	40 + ⊕	B.138,140
CMCE / CMSH 16 A	6 + 2 (aux.) + ⊕	B.145,150
CX / CXC 80 A/16 A	4/0, 4/2 + ⊕	B.158-160
CX 40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ⊕	B.163-164, 168-169

*can be used only in bulkhead mounting housings

Accessories: see page E.197

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 04 T (4-slot sized MIXO frames)	C.95

180 °C Inserts size 77.27	Poles	Pages
CNE RY** 16 A	16 + ⊕	I.7
CP RY** 35 A	6 + ⊕	I.10
CX RY** 80 A	4 + ⊕	I.11
CX RY** 80 A/16 A	4/2 + ⊕	I.12

** >125 °C up to 180 °C