

C-TYPE series

Hoods – 1 lever – without gasket

size **44.27**
**Heavy-Duty
Applications**




CE UK



EN 60529	IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 1 lever, without gasket, side entry	MHO 06 LX20 MHO 06 LX25 CHO 06 LX16		M20 M25 Pg 16	
	Hoods, 1 lever, without gasket, top entry To be used only with a complete cable gland	MHV 06 LX20 MHV 06 LX25 CHV 06 LX16		M20 M25 Pg 16	

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Accessories:

CHCP 06
 Dust protection
 cover
 Page G.46