

Slim enclosures with C-TYPE lever

size **66.40**

Hoods – 2 levers

Heavy-Duty
Applications



CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 levers, without gasket, side entry To be used only with a complete cable gland	MHO 50 X25 MHO 50 X32 CHO 50 X		M25 M32 Pg 21	
	Hoods, 2 levers, without gasket, side or top entry, high construction To be used only with a complete cable gland	MFO 50 X25 MFO 50 X32 CFO 50 X CFO 50 X29	MFV 50 X25 MFV 50 X32 CFV 50 X CFV 50 X29	M25 M32 Pg 21 Pg 29	

C-TYPE

E

Inserts size (66.16) × 2	Poles	Pages
CDA 16 A	32 + ⊕	B.18
CDC 16 A	32 + ⊕	B.21
CSAH 16 A	32 + ⊕	B.26
CD 10 A	50 + ⊕	B.32
CDD 10 A	76 + ⊕	B.34