

## Slim enclosures – E-Xtreme®

size **66.40**









Hoods and covers – 4 pegs


2 000 hrs resistance  
in salt-spray testsAggressive  
Environments

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK

C<sup>RU</sup> ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 4 pegs, without gasket, side entry	<a href="#">MHOE 50.25</a> <a href="#">MHOE 50.32</a>		M25 M32	
	Hoods, 4 pegs, without gasket, side or top entry, high construction, with metal adapter	<a href="#">MAOE 50.32</a>	<a href="#">MAVE 50.32</a>	M32	
	Covers, 4 pegs, without gasket  For enclosures with 2 levers and gasket  with loop for hoods  or with eyelet for housings 	With loop <a href="#">CHCE 50 S</a>	With eyelet <a href="#">CHCE 50</a>		

Inserts size (66.16) × 2	Poles 	Pages
CDA	16 A	32 + ⊕ B.18
CDC	16 A	32 + ⊕ B.21
CSAH	16 A	32 + ⊕ B.26
CD	10 A	50 + ⊕ B.32
CDD	10 A	76 + ⊕ B.34