

C-TYPE series

Housings – 4 pegs – with gasket

size **104.27**
**Heavy-Duty
Applications**


CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Metal cover	Plastic cover	Entry	Dimension
	Bulkhead mounting housings, 4 pegs and gasket, with or without metal or plastic cover	CHI 24 CS	CHI 24 CP		
	Enclosures with plastic cover do not have UL approval	Without Cover	CHI 24 C		
	Surface mounting housings, 4 pegs and gasket, with metal or plastic cover	MHP 24 CS25 MHP 24 CS225 CHP 24 CS CHP 24 CS2	MHP 24 CP25 MHP 24 CP225 CHP 24 CP CHP 24 CP2	M25 M25 × 2 Pg 21 Pg 21 × 2	
	Enclosures with plastic cover do not have UL approval				
	Surface mounting housings, 4 pegs and gasket, with metal or plastic cover, high construction	MAP 24 CS32 MAP 24 CS232 MAP 24 CS40 MAP 24 CS240 CAP 24 CS CAP 24 CS2 CAP 24 CS29 CAP 24 CS229	MAP 24 CP32 MAP 24 CP232 MAP 24 CP40 MAP 24 CP240 CAP 24 CP CAP 24 CP2 CAP 24 CP29 CAP 24 CP229	M32 M32 × 2 M40 M40 × 2 Pg 21 Pg 21 × 2 Pg 29 Pg 29 × 2	
	Enclosures with plastic cover do not have UL approval				

Inserts size 104.27	Poles	Pages	Inserts size 104.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	24 + ⊕	B.41	CSS 16 A	24 + ⊕	B.121	MIXO modules	C.12-93
CCE 16 A	24 + ⊕	B.47	CT / CTSE* 16 A	24 + ⊕	B.129,133	CX 06 T (6-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	24 + ⊕	B.55,61	CT / CTS* 10 A	64 + ⊕	B.139,141		
CSHT 16 A	24 + ⊕	B.68	CMCE / CMSH 16 A	10 + 2 (aux.) + ⊕	B.146,151		
CQE / CQEY 16 A	46 + ⊕	B.75,85	CX 100 A/16 A	8/0 and 6/6 + ⊕	B.156-157		
CQEE 16 A	64 + ⊕	B.79	CX / CXC 80 A/16 A	4/8 + ⊕	B.161-162		
CD 10 A	64 + ⊕	B.91	*can be used only in bulkhead mounting housings				
CDD 10 A	108 + ⊕	B.97					
CDSH 10 A	42 + ⊕	B.105	*can be used only in bulkhead mounting housings				

Accessories:

CHCP 24
Dust protection
cover
Page G.46