

## E-Xtreme® – CKAE / MKAE

size **21.21**

Hoods – 2 pegs





2 000 hrs resistance  
in salt-spray testsAggressive  
Environments

EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 2 pegs, side entry Not suitable for CQ4 series inserts	<a href="#">MKAE VA20</a>	M20	
	Hoods, 2 pegs, top entry Not suitable for CQ4 series inserts	<a href="#">MKAE V20</a>	M20	

CKAE / MKAE

A

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25

**Note:** to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12

**Accessories:**

**CKR 65**  
gasket and screw kits for  
IP66 / IP67 / IP69  
Page A.67