Metallic - CKA / MKA

Housings - 1 lever - with fixing thread

size **21.21**





EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C +125 °C
Mechanical life (cycles)	≥ 500

Description









Entry

M32

M32

M32

c% ECBT2.E115072 | ECBT8.E115072



Bulkhead mounting housings, 1 stainless steel lever, M32 fixing thread

- Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic)

With o-ring gasket


Part No.

MKAX IF

With flange gasket and locknut

MKAX IFC

M32





Bulkhead mounting housings, 1 stainless steel rigid lever or 1 galvanized rigid lever, M32 fixing thread, with o-ring

- Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic)


CQC, DNV, BV and cURus pending

Stainless steel rigid lever

MKAXX IF

Galvanized rigid lever

MKA IF M32





Bulkhead mounting housings, 1 stainless steel rigid lever or 1 galvanized rigid lever, M32 fixing thread, with flange gasket and locknut


CQC, DNV, BV and cURus pending

Stainless steel rigid lever

Galvanized rigid lever

MKAXX IFC

MKA IFC M32








Angled bulkhead mounting housings, 1 stainless steel lever, fixing thread with O-ring gasket

- Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic)

Not suitable for CQ4 series inserts

MKAX IAF20 M20 MKAX IAF25 M25







Angled bulkhead mounting housings, 1 galvanized rigid lever, fixing thread with O-ring gasket

- Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic)

MKA IAF20 MKA IAF25

M20 M25



(-						- /
Not	suitabl	e for	CQ4	serie	s ins	erts
CQ	C, DNV	, BV a	and c	URus	pen	ding

Accessories:

	32,5 —		1 26,5
4		PI	10
	– M →		+

Compact 21.21 li	nserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	2 to 21 + ⊕	A.4-12
CK / JK / CKSH	10 A	3 to 4 + ⊕	A.16-19
CD / CDY	10 A	8	A.24-25
CJ (RJ45)	1 A to 2,1 A	-	A.30-33
CUK (USB)	-	-	A.36
CX (BUS)	10 A	-	A.37
CLK (Fibre optics)	_	4	A.38

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12 - CJ KF

- CUK 2FT /3FT - CX 1/2 BDF/M

- CJK 8FT /8IFT

- CLK 04 SCF /SCF-H /SCM

CKR 65

gasket and screw kits for IP66 / IP67 / IP69 Page A.67