

EMC series – Electromagnetic Shielding

size **21.21**

Housings – 1 lever – with fixing thread

Specialized
Applications







EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



CIRIUS

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Bulkhead mounting housings, 1 stainless steel lever, M32 fixing thread - Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic)	MKAXS IF	M32	
	Bulkhead mounting housings, 1 stainless steel rigid lever, M32 fixing thread - Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic) CQC, DNV, BV and cURus pending	MKAXXS IF	M32	
	Bulkhead mounting housings, 1 galvanized rigid lever, M32 fixing thread - Locknut supplied on request, see Cable glands catalogue (article AS M32N metallic) CQC, DNV, BV and cURus pending	MKAS IF	M32	

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.24-25

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67