

Thermoplastic – CK / MK

Hoods – 2 pegs









size **21.21**
**Heavy-Duty
Applications**


EN 60529	IP44
With CKR 65	IP66 / IP67 / IP69
UL 50 / UL 50E	Type 12
With CKR 65	Type 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

CE UK



ECBT2.E115072 | ECBT8.E115072

Item	Description	Light grey	Jet black	Entry	Dimension
 	Hoods, 2 pegs, side entry Not suitable for CQ4 series inserts	MK VA20 CK 03 VAS	MK VAN20 CK 03 VANS	M20 Pg 11	 
 	Hoods, 2 pegs, top entry Not suitable for CQ4 series inserts	MK V20 CK 03 VS	MK VN20 CK 03 VNS	M20 Pg 11	 
 	Hoods, 2 pegs, side entry	MK VA25	MK VAN25	M25	 
 	Hoods, 2 pegs, top entry	MK V25	MK VN25	M25	 

Compact 21.21 Inserts	Poles	Pages
CQ4 / CQ / CQY	40 A to 6,5 A	A.4-12
CK / JK / CKSH	10 A	A.16-19
CD / CDY	10 A	A.22-23
CD / CDY	10 A	A.24-25

Note: to obtain the IP66 / IP67 / IP69 degree of protection it is necessary to replace the fixing screw supplied with all inserts, with the one with gasket included in the CKR 65 kit, to be purchased separately, except for the inserts listed below (already supplied with a fixing screw with gasket):

- CQF/M 07, CQF/M 12

Accessories:



CKR 65
gasket and screw kits for
IP66 / IP67 / IP69
Page A.67