

IL-BRID series

Housings and covers – 1 lever – with gasket

size **44.27**Heavy-Duty
Applications

CE UK

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



(pending CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	CLI 06 L	CLI 06 LS		
	Surface mounting housings, 1 lever and gasket, with or without metal cover	MLP 06 L20 MLP 06 L220	MLP 06 LS20 MLP 06 LS220	M20 M20 × 2	
	Surface mounting housings, 1 lever and gasket, with or without metal cover high construction To be used only with a complete cable gland	MLAP 06 L25 MLAP 06 L225 MLAP 06 L32 MLAP 06 L232 MLAP 06 L40 MLAP 06 L240	MLAP 06 LS32 MLAP 06LS232 MLAP 06 LS40 MLAP 06LS240	M25 M25 × 2 M32 M32 × 2 M40 M40 × 2	
	Covers, 1 lever and gasket For enclosures with 2 pegs without gasket with loop for hoods	CLC 06 LG			

Inserts size 44.27	Poles	Pages
CNE	16 A 6 + ⊕	B.38
CCE	16 A 6 + ⊕	B.44
CSH / JSH S	16 A 6 + ⊕	B.52,58
CQE / CQEY	16 A 10 + ⊕	B.72,82
CDD	10 A 24 + ⊕	B.94
CDSH / CDSH NC	10 A 9 and 6 + ⊕	B.102,108
CSS	16 A 6 + ⊕	B.118
CT / CTSE*	16 A 6 + ⊕	B.126,130

*can be used only in bulkhead mounting housings

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Complete with:

Hoods
Page E.49Covers
Page E.52