

IL-BRID series

Hoods – 1 lever – with gasket

size **57.27**
**Heavy-Duty
Applications**

CE UK




EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



(pending CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 1 lever and gasket, top entry		MLV 10 LG25	M25	
	Hoods, 1 lever and gasket, top entry, high construction, with metal adapter		MLAV 10 LG25 MLAV 10 LG32	M25 M32	
	Hoods, 1 lever and gasket, side or top entry, high construction To be used only with a complete cable gland	MLFO 06 LG40	MLFV 10 LG25 MLFV 10 LG32 MLFV 10 LG40	M25 M32 M40	

IL-BRID

E

Inserts size 57.27	Poles	Pages	Inserts size 57.27	Poles	Pages
CNE	16 A	10 + ☉ B.39	CMCE / CMSH	16 A	3 + 2 (aux.) + ☉ B.144,149
CCE	16 A	10 + ☉ B.45	CX	40 A/10 A	8/24 + ☉ B.170-171
CSH / JSH S	16 A	10 + ☉ B.53,59			
CSHT	16 A	10 + ☉ B.66			
CQE / CQEY	16 A	18 + ☉ B.73,83			
CDD	10 A	42 + ☉ B.95			
CDSH	10 A	18 + ☉ B.103			
CSS	16 A	10 + ☉ B.119			
			MIXO Modular Inserts		Pages
			MIXO modules		C.12-93
			CX 03 T (3-slot sized MIXO frames)		C.95

Complete with:


Hoods
Page E.55

Covers
Page E.60