



IL-BRID series

Hoods – 1 lever – without gasket

size **44.27****Heavy-Duty
Applications****CE UK**



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



(pending CQC)



ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 1 lever, without gasket, side entry	MLO 06 LX20 MLO 06 LX25	M20 M25	
	Hoods, 1 lever, without gasket, top entry	MLV 06 LX20 MLV 06 LX25	M20 M25	

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE	16 A	6 + ⊕	B.38	
CCE	16 A	6 + ⊕	B.44	
CSH / JSH S	16 A	6 + ⊕	B.52,58	
CQE / CQEY	16 A	10 + ⊕	B.72,82	
CDD	10 A	24 + ⊕	B.94	
CDSH / CDSH NC	10 A	9 and 6 + ⊕	B.102,108	
CSS	16 A	6 + ⊕	B.118	

Complete with:**Housings**
Page E.50**Covers**
Page E.52