

IL-BRID series

Housings and covers – 1 lever – with gasket

size **104.27**Heavy-Duty
Applications

CE UK

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500

(pending CQC)

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	With cover	Entry	Dimension
	Bulkhead mounting housings, 1 lever and gasket, with or without metal cover	CLI 24 L	CLI 24 LS		
	Surface mounting housings, 1 lever and gasket, with or without metal cover	MLP 24 L25 MLP 24 L225	MLP 24 LS25 MLP 24 LS225	M25 M25 × 2	
	Surface mounting housings, 1 lever and gasket, with or without metal cover high construction	MLAP 24 L32 MLAP 24 L232 MLAP 24 L40 MLAP 24 L240	MLAP 24 LS32 MLAP 24 LS232 MLAP 24 LS40 MLAP 24 LS240	M32 M32 × 2 M40 M40 × 2	
	Covers, 1 lever and gasket	CLC 24 LG			
	For enclosures with 2 pegs without gasket with loop for hoods				

Inserts size 104.27	Poles	Pages	Inserts size 104.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	24 + ⊕	B.41	CSS 16 A	24 + ⊕	B.121	MIXO modules	C.12-93
CCE 16 A	24 + ⊕	B.47	CT / CTSE* 16 A	24 + ⊕	B.129,133	CX 06 T (6-slot sized MIXO frames)	C.95
CSH / JSH S 16 A	24 + ⊕	B.55,61	CT / CTS* 10 A	64 + ⊕	B.139,141		
CSHT 16 A	24 + ⊕	B.68	CMCE / CMSH 16 A	10 + 2 (aux.) + ⊕	B.146,151		
CQE / CQEQ 16 A	46 + ⊕	B.75,85	CX 100 A/16 A	8/0 and 6/6 + ⊕	B.156-157		
CQEE 16 A	64 + ⊕	B.79	CX / CXC 80 A/16 A	4/8 + ⊕	B.161-162		
CD 10 A	64 + ⊕	B.91	*can be used only in bulkhead mounting housings				
CDD 10 A	108 + ⊕	B.97					
CDSH 10 A	42 + ⊕	B.105					

Complete with:

Hoods
Page E.71Covers
Page E.76