

Slim enclosures with IL-BRID lever

size **66.16**

Hoods and covers – 2 pegs

**Heavy-Duty
Applications**








CE UK



EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 500



ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, with gasket, side entry	MZO 25 L20 MZO 25 L25 CZO 25 L		M20 M25 Pg 16	
	Hoods, 2 pegs, with gasket, top entry To be used only with a complete cable gland		MZV 25 L20 CZV 25 L	M20 Pg 16	
 	Hoods, 2 pegs, with gasket, side or top entry, high construction To be used only with a complete cable gland	MZFO 25 L20 MZFO 25 L25 CZFO 25 L16 CZFO 25 L21	MZFV 25 L20 MZFV 25 L25 CZFV 25 L16 CZFV 25 L21	M20 M25 Pg 16 Pg 21	
 	Hoods, 2 pegs, with gasket, 2 top entries, high construction To be used only with complete cable glands Hoods, 2 pegs, with gasket, high construction, designed to be drilled		Without entry CZAC 25 L	M20 × 2 Pg 16 × 2	
	Covers, 2 pegs, with gasket For enclosures with 1 lever without gasket with loop for hoods  or with eyelet for housings 	With loop CZC 25 SL	With eyelet CZC 25 L		

Inserts size 66.16		Poles	Pages
CDA	16 A	16 + ⊕	B.17
CDC	16 A	16 + ⊕	B.20
CSAH	16 A	16 + ⊕	B.25
CD	10 A	25 + ⊕	B.31
CDD	10 A	38 + ⊕	B.33