

HNM series – High Number of Mating cycles

size **44.27**

Hoods – 2 anti-friction pegs – without gasket





Specialized
Applications


CE UK

DNV BUREAU
VERITAS

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 / 4 / 4X
Ambient temperature limits	-40 °C ... +125 °C
Mechanical life (cycles)	≥ 10 000

cALUS ECBT2.E115072 | ECBT8.E115072

Item	Description	Side entry	Top entry	Entry	Dimension
	Hoods, 2 pegs, without gasket, side entry	RHO 06 L25		M25	
	Hoods, 2 pegs, without gasket, top entry		RHV 06 L25	M25	
	Hoods, 2 pegs, without gasket, side or top entry, high construction	RFO 06 L32	RFV 06 L32	M32	
	Hoods, 2 pegs, without gasket, high construction, designed to be drilled	Without entry			

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
RCE 16 A	6 + ⊕	H.10	MIXO HNM modules	H.38-60
RSH 16 A	6 + ⊕	H.14	RX 02 T (2-slot sized MIXO HNM frames)	H.62
RDD 10 A	24 + ⊕	H.22		
RDSH 10 A	9 + ⊕	H.26		

Accessories:


CR 06 DF
Self-centring floating
frame HNM
Page H.64