

T-TYPE Hygienic series – Food and Beverage

size **44.27**

T-TYPE/H Housings and hoods for production lines

T-TYPE/C Housings and hoods for low-temperatures





Specialized
Applications

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 – Type 4 / 4X Indoor Use Only
Ambient temperature limits	T-TYPE/H: -40 °C ... +70 °C T-TYPE/C: -50 °C ... +70 °C
Mechanical life (cycles)	≥ 500

CE UK

(pending: CQC)

ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE/H	T-TYPE/C	Entry	Dimension
	Bulkhead mounting housings, 1 lever	THIH 06 L	THIC 06 L		
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				
	Surface mounting housings, 1 lever, high construction	TAPH 06 L25 TAPH 06 L32	TAPC 06 L25 TAPC 06 L32	M25 M32	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).				
	Hoods, 1 lever and gasket, top entry, high construction	TAVH 06 LG25 TAVH 06 LG32	TAVC 06 LG25 TAVC 06 LG32	M25 M32	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE	16 A	6 + ⊕	B.38	
CCE	16 A	6 + ⊕	B.44	
CSH / JSH S	16 A	6 + ⊕	B.52,58	
CQE / CQEY	16 A	10 + ⊕	B.72,82	
CDD	10 A	24 + ⊕	B.94	
CDSH / CDSH NC	10 A	9 and 6 + ⊕	B.102,108	
CSS	16 A	6 + ⊕	B.118	

MIXO Modular Inserts	Pages
MIXO modules	C.12-93
CX 02 T (2-slot sized MIXO frames)	C.95

Complete with:


Hoods
Page E.227

Covers
Page E.235

PE jumpers
(Optional)
Page E.249