

T-TYPE Hygienic series – Food and Beverage

size **77.27**

T-TYPE/H Housings and hoods for production lines

T-TYPE/C Housings and hoods for low-temperatures

Specialized
Applications

EN 60529	IP65 / IP66 / IP69
UL 50 / UL 50E	Type 12 – Type 4 / 4X Indoor Use Only
Ambient temperature limits	T-TYPE/H: -40 °C ... +70 °C T-TYPE/C: -50 °C ... +70 °C
Mechanical life (cycles)	≥ 500

CE UK

(pending: CQC)

ECBT2.E115072 | ECBT8.E115072

Item	Description	T-TYPE/H	T-TYPE/C	Entry	Dimension
	Bulkhead mounting housings, 2 levers	THIH 16	THIC 16		
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				
	Surface mounting housings, 2 levers, high construction	TAPH 16.32 TAPH 16.40	TAPC 16.32 TAPC 16.40	M32 M40	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C Supplied with an open threaded entry and diametrically opposite a closed threaded entry which can be opened by the user if required (with suitable tool).				
	Hoods, 2 levers and gasket, top entry, high construction	TAVH 16 G32 TAVH 16 G40	TAVC 16 G32 TAVC 16 G40	M32 M40	
	- HNBR gasket for T-TYPE/H - SILICONE gasket for T-TYPE/C				

Inserts size 77.27	Poles	Pages	Inserts size 77.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE	16 A	16 + ☉ B.40	CP / CPY	35 A	6 + ☉ B.112,114	MIXO modules	C.12-93
CCE	16 A	16 + ☉ B.46	CSS	16 A	16 + ☉ B.120	CX 04 T (4-slot sized MIXO frames)	C.95
CSH / JSH S	16 A	16 + ☉ B.54,60	CMCE / CMSH	16 A	6 + 2 (aux.) + ☉ B.145,150		
CSHT	16 A	16 + ☉ B.67	CX / CXC	80 A/16 A	4/0, 4/2 + ☉ B.158-160		
CQE / CQEY	16 A	32 + ☉ B.74,84					
CQEE	16 A	40 + ☉ B.78	CX	40 A/10 A	6/12, 6/36, 9/42 and 12/2 + ☉ B.163-164, 168-169		
CD	10 A	40 + ☉ B.90					
CDD	10 A	72 + ☉ B.94					
CDSH	10 A	27 + ☉ B.104					

Complete with:

Hoods
Page E.231Covers
Page E.235PE jumpers
(Optional)
Page E.249