

T-TYPE series – Insulating

Hoods – 2 pegs

size **44.27**

Aggressive
Environments



Heavy-Duty
Applications





EN 60529	IP65
UL 50 / UL 50E	Type 12
Ambient temperature limits	-40 °C ... +90 °C
Mechanical life (cycles)	≥ 500

CE UK



CEC

ECBT2.E115072 | ECBT8.E115072

Item	Description	Part No.	Entry	Dimension
	Hoods, 2 pegs, side entry, high construction, without gasket	TMAO 06 L25 TMAO 06 L32	M25 M32	
	Hoods, 2 pegs, top entry, high construction, without gasket	TMAV 06 L25 TMAV 06 L32	M25 M32	

Inserts size 44.27	Poles	Pages	MIXO Modular Inserts	Pages
CNE 16 A	6 + ⊕	B.38	MIXO modules	C.12-93
CCE 16 A	6 + ⊕	B.44	CX 02 T (2-slot sized MIXO frames)	C.95
CSH / JSH S	16 A	6 + ⊕		
CQE / CQEY	16 A	10 + ⊕		
CDD	10 A	24 + ⊕		
CDSH / CDSH NC	10 A	9 and 6 + ⊕		
CSS	16 A	6 + ⊕		

Accessories:



CR BPE
PE jumpers

Page E.236