



Signal Towers Overview














SIGNAL TOWERS

Whether for access control or use on machinery, systems and manual workstations - WERMA signal towers are available in a variety of colours, functions, sizes and shapes. Customers can find unique solutions with excellent design quality also for use in strict hygiene areas. Various escalation levels in the event of a problem can be signalled thanks to the multi-tier design of the signal towers. This allows employees in the vicinity to respond quickly to a malfunction and rectify the problem.

Select the ideal signal tower for your application on the following pages.

Overview Signal Towers

		TwinLIGHT TwinFLASH 	TwinLIGHT TwinFLASH	
				
Modularity		modular	modular	modular
Technical details		KombiSIGN 40	KombiSIGN 72	KombiSIGN 71
Diameter		40 mm	70 mm	70 mm
Dimensions	Ø x Height (max.)	40 mm x 313 mm	70 mm x 323 mm	70 mm x 323 mm
	L x H x W	—	—	—
Voltage	12 V	—	—	—
	24 V	✓	✓	✓
	115 V	—	—	✓
	230 V	—	—	✓
Protection rating		IP 66	IP 65	IP 65
Operating temperature	-20°C...+50°C	✓	✓	✓
	-30°C...+50°C	✓	—	—
	-30°C...+60°C	✓	✓	—
Number of optical tiers possible		1-5	1-5	1-5
Light effect	Permanent light	✓ (TwinLIGHT)	✓ (TwinLIGHT)	✓
	Permanent light ultrabright	—	—	✓
	Blinking light	✓ (TwinLIGHT)	✓ (TwinLIGHT)	✓
	Flash/Double flash/EVS	✓ (TwinFLASH)	✓ (TwinFLASH)	✓
	Rotating light	—	—	✓
	Multicolour	✓ (TwinFLASH)	✓ (TwinFLASH)	✓
Tone type		2/8 tone siren	2 tone siren/ sirens/ Vocal element	2/8 tone siren/ sirens/ Vocal element
Max. dB		95 dB	105 dB	105 dB
Mounting (without accessories)	Tube mounting	✓	✓	✓
	Base mounting	✓	✓	✓
	Single hole mounting	✓	—	—
	Bracket mounting	—	—	—
Housing colour	black	✓	✓	✓
	grey	✓	✓	—
Connection method	Spring type/push-in terminal	✓	✓	✓
	M12 Connector	—	—	✓
	Flying lead	—	—	—
Interface		I/O Link	Asi, USB, SmartMONITOR, AndonSPEED	Asi, USB, SmartMONITOR, AndonSPEED

				
Modularity		pre-assembled	pre-assembled	pre-assembled
Technical details		KOMPAKT 37	ClearSIGN	CleanSIGN
Diameter		37,5 mm	40 mm	70 mm
Dimensions	Ø x Height (max.)	37,5 mm x 230 mm	104 mm x 320 mm	—
	L x H x W	—	—	152 mm x 485 mm x 112 mm
Voltage	12 V	✓	—	—
	24 V	✓	✓	✓
	115 V	—	—	—
	230 V	—	—	—
Protection rating		IP 65	IP 66	IP 67/IP 69k
Operating temperature	-20°C...+50°C	✓	✓	✓
	-30°C...+50°C	—	—	✓
	-30°C...+60°C	—	—	—
Number of optical tiers possible		1-5	4	3
Light effect	Permanent light	✓	✓	✓
	Permanent light ultrabright	—	—	—
	Blinking light	—	—	✓
	Flash/Double flash/EVS	—	—	✓
	Rotating light	—	—	—
	Multicolour	—	✓	✓
Tone type		Pulse tone	Continuous tone	Continuous tone
Max. dB		85 dB	85 dB	85 dB
Mounting (without accessories)	Tube mounting	—	—	—
	Base mounting	—	✓	✓
	Single hole mounting	✓	—	—
	Bracket mounting	—	—	✓
Housing colour	black	✓	—	✓
	grey	✓	✓	—
Connection method	Spring type/push-in terminal	—	✓	—
	M12 Connector	✓	—	—
	Flying lead	✓	—	✓
Interface		—	I/O Link	—

KombiSIGN 40 - Modular Signal Tower

The new, modular KombiSIGN 40 has been designed with mechanical engineers and automation specialists in mind who not only want to rely on safe and reliable signals but also have their eye on cost in terms of assembly, logistics and worldwide part provision. Available in DesignLOOK or ClassicLOOK. Optionally available with IO-Link technology.

- Save up to 50% on installation time thanks to self-explanatory connections and intuitive mechanics
- TwinLIGHT and TwinFLASH combine two easily selectable light effects in one element
- Clearly visible from all positions thanks to the OmniVIEW lens with no blind spots

TwinLIGHT
TwinFLASH



MODULAR SIGNAL TOWERS

Optical and audible signal elements can be combined flexibly in the modular signal towers. The modular design also enables customers to retrofit other elements separately when required.

- 1 Select the required optical or audible elements or select a pre-configured signal tower.
- 2 Select the terminal element.
- 3 Where appropriate, select up to two extension tubes. Can be installed between the terminal element and the mounting adapter.
- 4 Select the appropriate mounting option for your application.
- 5 Where appropriate, select the bracket.


KombiSIGN 40 - Quickfinder 24 V AC/DC

ClassicLOOK


1

 8 tone siren Order no. 635 810 75	 TwinLIGHT white Order no. 634 430 75 TwinFLASH white Order no. 634 440 55
 2 tone siren Order no. 635 800 75	 TwinLIGHT blue Order no. 634 510 75 TwinFLASH blue Order no. 634 520 55
 TwinLIGHT red Order no. 634 110 75 TwinFLASH red Order no. 634 120 55	 LED permanent light multicolour Order no. 634 450 55
 TwinLIGHT green Order no. 634 210 75 TwinFLASH green Order no. 634 220 55	 Pre-assembled signal tower TwinLIGHT green/yellow/red Order no. 639 300 01 --> continue with 4
 TwinLIGHT yellow Order no. 634 310 75 TwinFLASH yellow Order no. 634 320 55	

2

 Terminal element Order no. 630 800 75
--

3

 Extension tube Order no. 960 630 03
--










4

Tube mounting	Single hole mounting	Base mounting
 Adapter for Tube mounting Order no. 630 830 00	 Adapter for Single hole mounting Order no. 630 820 00	 Adapter for Base mounting Order no. 630 810 00


5




 Bracket for assembly on aluminium profiles Order no. 960 630 02	 Bracket for concealed cable entry Order no. 960 630 01
--	---

DesignLOOK

 8 tone siren Order no. 635 710 75	 TwinLIGHT white Order no. 634 430 75 TwinFLASH white Order no. 634 440 55
 2 tone siren Order no. 635 700 75	 TwinLIGHT blue Order no. 634 530 75 TwinFLASH blue Order no. 634 540 55
 TwinLIGHT red Order no. 634 130 75 TwinFLASH red Order no. 634 140 55	 LED permanent light multicolour Order no. 634 450 55
 TwinLIGHT green Order no. 634 230 75 TwinFLASH green Order no. 634 240 55	 Pre-assembled signal tower TwinLIGHT green/yellow/red Order no. 639 301 01 --> continue with 4
 TwinLIGHT yellow Order no. 634 330 75 TwinFLASH yellow Order no. 634 340 55	

 Terminal element Order no. 630 700 75
--

 Extension tube Order no. 960 630 07
--

Tube mounting	Single hole mounting	Base mounting
 Adapter for Tube mounting Order no. 630 730 00	 Adapter for Single hole mounting Order no. 630 720 00	 Adapter for Base mounting Order no. 630 710 00

 Bracket for assembly on aluminium profiles Order no. 960 630 06	 Bracket for concealed cable entry Order no. 960 630 05
--	---

You can find more accessories in our signal tower configurator at www.werma.com as well as the most popular pre-assembled signal tower options with just one part number (also available for KombiSIGN 72 and 71).

KombiSIGN 72 - Modular Signal Tower

There is no need to compromise with the KombiSIGN 72, because this product combines quick installation, excellent visibility and the highest level of flexibility. This saves time and money with regard to installation and order logistics.


- Smooth surfaces prevent dirt gathering and make cleaning easy
- Easy, intuitive installation - incorrect assembly is practically impossible (Poka Yoke)
- High-tech: the Signal Towers can easily be retro-fitted with SmartMONITOR (smart MDE alternative) or AndonSPEED (call for action system)
- TwinLIGHT and TwinFLASH combine two easily selectable light effects in one element





TwinLIGHT
TwinFLASH

- 1 Select the required optical or audible elements or select a pre-configured signal tower.
- 2 Select the appropriate mounting option for your application.
- 3 Select the correct terminal element for your mounting option.
- 4 Where appropriate, select a base and the desired tube length (only for tube mounting).
- 5 Where appropriate, select the bracket and the contact box.

ClassicLOOK - pre-assembled

Base mounting	Tube mounting
 <p>TwinLIGHT - 24 V AC/DC green/yellow/red Order no. 649 000 01</p>	 <p>TwinLIGHT - 24 V AC/DC green/yellow/red Order no. 649 000 02</p>

DesignLOOK - pre-assembled

Base mounting	Tube mounting
 <p>TwinLIGHT - 24 V AC/DC green/yellow/red Order no. 649 001 01</p>	 <p>TwinLIGHT - 24 V AC/DC green/yellow/red Order no. 649 001 02</p>

KombiSIGN 72 - Quickfinder 24 V AC/DC

ClassicLOOK

1



2 tone siren
Order no. **645 870 75**



TwinLIGHT yellow
Order no. **647 310 75**
TwinFLASH yellow
Order no. **647 320 55**



TwinLIGHT red
Order no. **647 110 75**
TwinFLASH red
Order no. **647 120 55**



TwinLIGHT white
Order no. **647 430 75**
TwinFLASH white
Order no. **647 440 55**



TwinLIGHT green
Order no. **647 210 75**
TwinFLASH green
Order no. **647 220 55**



TwinLIGHT blue
Order no. **647 510 75**
TwinFLASH blue
Order no. **647 520 55**

DesignLOOK



2 tone siren
Order no. **645 770 75**



TwinLIGHT yellow
Order no. **647 330 75**
TwinFLASH yellow
Order no. **647 340 55**



TwinLIGHT red
Order no. **647 130 75**
TwinFLASH red
Order no. **647 140 55**



TwinLIGHT white
Order no. **647 430 75**
TwinFLASH white
Order no. **647 440 55**



TwinLIGHT green
Order no. **647 230 75**
TwinFLASH green
Order no. **647 240 55**



TwinLIGHT blue
Order no. **647 530 75**
TwinFLASH blue
Order no. **647 540 55**

2

Base mounting

Tube mounting

Base mounting

Tube mounting

3



Terminal element with
CAGE CLAMP® technology
Order no. **640 800 00**



Terminal element with
CAGE CLAMP® technology
Order no. **640 810 00**



Terminal element with
CAGE CLAMP® technology
Order no. **640 900 00**



Terminal element with
CAGE CLAMP® technology
Order no. **640 910 00**

4



Base with
integrated tube
Order no.
975 840 10

Tube Ø 25 mm, all anodized
Order no.
100 mm long **975 845 10**
250 mm long **975 840 25**
400 mm long **975 840 40**
600 mm long **975 840 60**
800 mm long **975 840 80**
1000 mm long **975 840 03**

Base for tube, plastic
Order no. **975 840 90**

Base for tube, metal
Order no. **975 840 91**



Base with
integrated tube
Order no.
960 000 51

Tube Ø 25 mm, all anodized
Order no.
100 mm long **975 845 10**
250 mm long **975 840 25**
400 mm long **975 840 40**
600 mm long **975 840 60**
800 mm long **975 840 80**
1000 mm long **975 840 03**

Base for tube, plastic
Order no. **960 000 50**



5



Bracket for base mounting
Order no. **960 000 02**



Bracket for 1-sided
mounting
Order no. **975 840 85**



Bracket for 2-sided
mounting
Order no. **975 840 86**



Bracket for base mounting
with concealed cable
entry
Order no. **960 000 14**



Bracket for
tube mounting
Order no. **960 000 01**



Bracket for base mounting
Order no. **960 000 53**



Bracket for 1-sided mounting
Order no. **960 000 52**



Bracket for base mounting
with concealed
cable entry
Order no. **960 000 55**



Bracket for
tube mounting
Order no. **960 000 54**

You can find more accessories in our signal tower configurator at www.verma.com as well as the most popular pre-assembled signal tower options with just one part number (also available for KombiSIGN 40 and 71).

KombiSIGN 71 - Modular Signal Tower

Profit from the wide range of optical and audible signal elements with the modular KombiSIGN 71. Its patented bayonet locking mechanism makes it easy to assemble and disassemble as well as exchange elements in a matter of seconds.

- A wide range of accessories ensures maximum flexibility
- High-tech: The Signal Towers can easily be retrofitted with SmartMONITOR (intelligent MDE alternative) or AndonSPEED (call for action system)



- 1 Select the required optical or audible elements or select a pre-configured signal tower.
- 2 Select the appropriate mounting option for your application.
- 3 Select the correct terminal element for your mounting option.
- 4 Where appropriate, select a base and the desired tube length (only for tube mounting).
- 5 Where appropriate, select the bracket and the contact box.

Pre-assembled signal towers

Base mounting	Tube mounting	Base mounting	Tube mounting
			
LED permanent light - green/red 24 V AC/DC Order no. 649 240 04	LED permanent light - green/red 24 V AC/DC Order no. 649 240 06	LED permanent light - green/yellow/red 24 V AC/DC Order no. 649 240 02	LED permanent light - green/yellow/red 24 V AC/DC Order no. 649 240 05

KombiSIGN 71 - Quickfinder 24 V AC/DC

1



Buzzer
Order no. **645 800 75**
8 tone siren
Order no. **645 820 75**



LED permanent light yellow
Order no. **644 300 75**
LED blinking light yellow
Order no. **644 310 75**



LED permanent light white
Order no. **644 400 75**
LED blinking light white
Order no. **644 410 75**



LED permanent light red
Order no. **644 100 75**
LED blinking light red
Order no. **644 110 75**



LED permanent light green
Order no. **644 200 75**
LED blinking light green
Order no. **644 210 75**



LED permanent light blue
Order no. **644 500 75**
LED blinking light blue
Order no. **644 510 75**

2

Base mounting

3



Terminal element with
CAGE CLAMP® technology
Order no. **640 800 00**



Screw terminal
Order no. **640 820 00**



Terminal element M12
Order no. **640 850 55**

Tube mounting



Terminal element with
CAGE CLAMP® technology
Order no. **640 810 00**



Screw terminal
Order no. **640 830 00**



Terminal element M12
Order no. **640 860 55**

4



Tube with
clamp
Order no.
960 000 18



Adapter für
Single hole
mounting
Order no.
960 000 25



Base with
integrated
tube
Order no.
975 840 10



Tube Ø 25 mm, all anodized
Order no.
100 mm long **975 845 10**
250 mm long **975 840 25**
400 mm long **975 840 40**
600 mm long **975 840 60**
800 mm long **975 840 80**
1000 mm long **975 840 03**



Base for tube, plastic
Order no. **975 840 90**



Base for tube, metal
Order no. **975 840 91**



Foldaway Base
Order no. **960 000 30**



Foldaway Base
Order no. **960 009 12**



Tube Ø 25 mm, plastic, only for Foldaway Base, 45 mm long
Order no. **960 000 31**

5



Contact box for cable exit at side
Order no. **975 840 01**



Bracket for base mounting
Order no. **960 000 02**



Bracket for 1-sided mounting
Order no. **975 840 85**



Bracket for 2-sided mounting
Order no. **975 840 86**



Corner fixing bracket
Order no. **960 000 41**



Contact box for cable exit at side
Order no. **975 840 01**



Contact box with magnetic base
and cable exit at side
Order no. **975 840 04**



Bracket for base mounting
with concealed cable entry
Order no. **960 000 14**



Bracket for tube mounting
Order no. **960 000 01**



Corner fixing bracket
Order no. **960 000 41**

Further options for light elements, audible elements, accessories and voltages can be found at www.werma.com or in the current catalogue. Here you will also find the most popular pre-assembled signal tower options with just one part number (also available for KombiSIGN 40 and 72).

ClearSIGN - Pre-assembled Signal Tower

The pre-assembled ClearSIGN signal tower combines industry design with the latest cutting-edge LED technology and innovative interfaces. The signal tower is ideally suited to modern industrial environments.

- With 4 tiers
- Maximum range of colours using RGB Technology
- Visual display of fill levels and temperature conditions
- Set colours and light effects according to your needs with the IO-Link version

Buzzer module
Order no. **656 000 55**

red/yellow/green/blue
Order no. **656 000 03**

RGB
Order no. **656 100 01**

IO Link without buzzer
Order no. **656 100 02**

IO Link Version with buzzer
Order no. **656 100 03**

PRE-ASSEMBLED SIGNAL TOWERS

Pre-assembled signal towers from WERMA come ready assembled and can be ordered as a compact unit with just one single number. Impressive features include their stylish design and diverse installation options, allowing them to be used in a wide range of areas.



 **IO-Link**

CleanSIGN - Pre-assembled Signal Tower

The CleanSIGN signal tower has been specifically developed and certified for use in clean rooms, food and hygiene areas as well as the pharmaceutical industry. The signal tower ensures maximum safety in these environments by reducing the risk of contamination.

- Easy-to-clean, hygienic design for optimal cleaning and disinfection
- Ensures food safety through the absence of uneven surfaces, elevated or countersunk elements where dirt can accumulate
- Use of food safe materials and resistant to cleaning agents (FDA approved)



Wall mounting



red/green/yellow
Order no. **695 300 55**

RGY
Order no. **695 200 55**

RGB
Order no. **695 000 55**

Base/Ceiling mounting



red/green/yellow
Order no. **695 310 55**

RGY
Order no. **695 210 55**

RGB
Order no. **695 010 55**

KOMPAKT 37- Pre-assembled Signal Tower

The streamline KOMPAKT 37 can be ordered pre-assembled with just one single order number. It is also available with a M12 plug or cable connection, making it the perfect signal tower for whatever the application.

- With 1 to 5 tiers
- Up to six levels of signal escalation possible – including an audible signal
- In ClassicLOOK or DesignLOOK to suit all machine surfaces
- Clearly visible from all positions thanks to the OmniVIEW lens with no blind spots



- 1 Select the signal tower of your choice with or without buzzer, with the appropriate connection, housing colour, voltage and number of tiers.
- 2 Select up to two extension tubes.
- 3 Select the appropriate fixing accessories for your application, using for example a tube and base or a bracket mounting.
- 4 Where appropriate, select the bracket and the contact box.

ClassicLOOK without buzzer

DesignLOOK without buzzer

1	ClassicLOOK without buzzer		DesignLOOK without buzzer	
	Plug	Cable	Plug	Cable
	2 tier (green/red) Order no. 698 220 75	2 tier (green/red) Order no. 698 120 75	2 tier (green/red) Order no. 698 420 75	2 tier (green/red) Order no. 698 320 75
	2 tier (yellow/red) Order no. 698 230 75	2 tier (yellow/red) Order no. 698 130 75	2 tier (yellow/red) Order no. 698 430 75	2 tier (yellow/red) Order no. 698 330 75
	3 tier (green/yellow/red) Order no. 698 210 75	3 tier (green/yellow/red) Order no. 698 110 75	3 tier (green/yellow/red) Order no. 698 410 75	3 tier (green/yellow/red) Order no. 698 310 75
	4 tier (clear/green/yellow/red) Order no. 698 240 75	4 tier (clear/green/yellow/red) Order no. 698 140 75	4 tier (clear/green/yellow/red) Order no. 698 440 75	4 tier (clear/green/yellow/red) Order no. 698 340 75
	4 tier (blue/green/yellow/red) Order no. 698 250 75	4 tier (blue/green/yellow/red) Order no. 698 150 75	4 tier (blue/green/yellow/red) Order no. 698 450 75	4 tier (blue/green/yellow/red) Order no. 698 350 75
	5 tier (blue/clear/green/yellow/red) Order no. 698 260 75	5 tier (blue/clear/green/yellow/red) Order no. 698 160 75	5 tier (blue/clear/green/yellow/red) Order no. 698 460 75	5 tier (blue/clear/green/yellow/red) Order no. 698 360 75

Continue with 2 - see next page.
Further voltage options can be found on our signal configurator at www.werma.com.

KOMPAKT 37 - Quickfinder 24 V AC/DC

ClassicLOOK with buzzer

DesignLOOK with buzzer

1	ClassicLOOK with buzzer		DesignLOOK with buzzer	
	Plug	Cable	Plug	Cable
	<p>1 tier (red) Order no. 699 610 75</p> <p>1 tier (yellow) Order no. 699 630 75</p> <p>2 tier (green/red) Order no. 699 220 75</p> <p>2 tier (yellow/red) Order no. 699 230 75</p> <p>3 tier (green/yellow/red) Order no. 699 210 75</p> <p>4 tier (clear/green/yellow/red) Order no. 699 240 75</p> <p>4 tier (blue/green/yellow/red) Order no. 699 250 75</p> <p>5 tier (blue/clear/green/yellow/red) Order no. 699 260 75</p>	<p>2 tier (green/red) Order no. 699 120 75</p> <p>2 tier (yellow/red) Order no. 699 130 75</p> <p>3 tier (green/yellow/red) Order no. 699 110 75</p> <p>4 tier (clear/green/yellow/red) Order no. 699 140 75</p> <p>4 tier (blue/green/yellow/red) Order no. 699 150 75</p> <p>5 tier (blue/clear/green/yellow/red) Order no. 699 160 75</p> 	<p>1 tier (red) Order no. 699 810 75</p> <p>1 tier (yellow) Order no. 699 830 75</p> <p>2 tier (green/red) Order no. 699 420 75</p> <p>2 tier (yellow/red) Order no. 699 430 75</p> <p>3 tier (green/yellow/red) Order no. 699 410 75</p> <p>4 tier (clear/green/yellow/red) Order no. 699 440 75</p> <p>4 tier (blue/green/yellow/red) Order no. 699 450 75</p> <p>5 tier (blue/clear/green/yellow/red) Order no. 699 460 75</p>	<p>2 tier (green/red) Order no. 699 320 75</p> <p>2 tier (yellow/red) Order no. 699 330 75</p> <p>3 tier (green/yellow/red) Order no. 699 310 75</p> <p>4 tier (clear/green/yellow/red) Order no. 699 340 75</p> <p>4 tier (blue/green/yellow/red) Order no. 699 350 75</p> <p>5 tier (blue/clear/green/yellow/red) Order no. 699 360 75</p> 
2	 <p>Extension tube Order no. 960 698 02</p>		 <p>Extension tube Order no. 960 698 04</p>	
3	Single hole mounting	Bracket mounting	Single hole mounting	Bracket mounting
	Base mounting	Base mounting	Base mounting	Base mounting
	 <p>Bracket for base mounting Order no. 960 630 02</p>	 <p>Base with integrated tube Order no. 960 698 01</p>	 <p>Bracket for base mounting Order no. 960 630 06</p>	 <p>Base with integrated tube Order no. 960 698 03</p>
4	 <p>Bracket for base mounting with concealed cable entry; Order no. 960 000 14</p>  <p>Bracket for tube mounting Order no. 960 000 01</p>  <p>Corner fixing bracket Order no. 960 000 41</p>  <p>Contact box for cable exit at side Order no. 975 840 01</p>  <p>Contact box with magnetic base and cable exit at side Order no. 975 840 04</p>		 <p>Bracket for base mounting with concealed cable entry Order no. 960 000 55</p>  <p>Bracket for tube mounting Order no. 960 000 54</p>	

WERMA Signaltechnik GmbH + Co. KG
Dürbheimer Str. 15
D-78604 Rietheim-Weilheim
Phone +49 7424 9557-0
Fax +49 7424 9557-44
www.werma.com
info@werma.com

WERMA Signaltechnik
Niederlassung Neuhausen am Rhf.
Rheingoldstrasse 50
8212 Neuhausen am Rheinfall
Switzerland
Phone +41 52 674 0060
Fax +41 52 674 0066
www.werma.ch
info@werma.ch

WERMA SARL
56, Rue Collière
69780 Mions
France
Phone +33 472 22 3737
Fax +33 472 22 3764
www.werma.fr
info@werma.fr

WERMA BENELUX bvba
Industrieweg 78-80 Bus 2
9032 Wondelgem
Belgium
Phone +32 220 31 11
Fax +32 222 81 11
www.wermabenelux.com
info@wermabenelux.com

WERMA (UK) Ltd.
11 Regent Park
37 Booth Drive
Park Farm Industrial Estate
Wellingborough NN8 6GR
Great Britain
Phone +44 1536 486930
Fax +44 1536 514810
www.werma.co.uk
uksales@werma.co.uk

WERMA USA Inc.
6731 Collamer Road
East Syracuse, NY 13057 USA
Phone +1 315 414 0200
Fax +1 315 414 0201
www.werma.com
us-info@werma.com

WERMA (Shanghai) Co., Ltd.
No. 8, High Technology Zone,
No. 503, Meinengda Road,
Songjiang, Shanghai, P. R. C
201613
China
Phone +86 21 5774-0022
Fax +86 21 5774-6601
www.werma.com.cn
info@werma.com.cn

